

Water Duct Type

PRODUCT:

- Ducted and non-ducted installations
- Static pressure from 50 to 110 Pa



Models			HAW-HAY														
			15			25			35			45					
Fan speed			HS	MS	LS	HS	MS	LS	HS	MS	LS	HS	MS	LS			
Cooling capacity	Total capacity	kW	7.07	6.83	6.57	9.40	8.64	8.07	12.32	11.90	11.54	15.30	15.07	14.77			
	Water flow	l/h	1,680			1,930			2,057			2,316					
	Pressure drop	kPa	13.44			15.67			19.55			29.94					
Heating capacity (2 tube)	Capacity	kW	7.70	7.35	7.00	10.32	9.14	8.32	13.86	13.38	12.63	17.22	16.82	16.35			
	Water flow	l/h	1,680			1,930			2,057			2,316					
	Pressure drop	kPa	13.44			15.67			19.55			29.94					
Fan section	Air flow	m ³ /h	1,359	1,274	1,189	1,750	1,495	1,308	2,497	2,378	2,190	3,090	2,980	2,880			
Acoustics	Noise level	dB(A)	50	42	39	53	45	43	54	49	45	58	55	52			
Electrical characteristics	Power supply	V/Ph/Hz	220-240/1/50 or 208-230/1/60														
		Hz	50	60	50	60	50	60	50	60	50	60					
	Power input	W	204	283	330	465	330	465	330	465	330	465					
	Nominal current	A	0.97	1.33	1.74	2.4	1.74	2.4	1.74	2.4	1.74	2.4					
Controls			Wired or wireless remote control with LCD display														
Dimensions	H	mm	305			325			350			350					
	W	mm	897			962			1,102			1,400					
	D	mm	567			628			640			640					
Net Operating weight		kg	51			53			66			88					
Water connections	Type		Male Water Pipe Thread														
	Diameter (nominal)		1/2"			3/4"			3/4"			3/4"					
Cooling capacity based on: 7°C EWT - Indoor air temp. 27°C DB / 19°C WB						Heating capacity based on: 45°C EWT - Indoor air temp. 20°C DB											

