

# Water High Wall

## PRODUCT:

- Modern and compact design
- Low noise
- Air sweep



Models			HHH-HHW-HHY								
			05			07			11		
		Fan speed	HS	MS	LS	HS	MS	LS	HS	MS	LS
Cooling capacity	Total capacity	kW	1.58	1.51	1.48	2.19	1.88	1.77	2.80	2.67	2.50
	Water flow	l/h	275			376			481		
	Pressure drop	kPa	15			26			40		
Heating capacity	Capacity	kW	2.53	2.42	2.37	3.50	3.01	2.83	5.52	5.28	4.93
	Water flow	l/h	271			376			481		
	Pressure drop	kPa	15			26			40		
Fan section	Air flow (high speed)	m <sup>3</sup> /h	300			390			670		
Electrical characteristics	Power supply	V/Ph/Hz	220-240/1/50								
	Power input	W	21			29			60		
	Nominal current	A	0.09			0.12			0.28		
Controls			Infrared remote control with LCD display								
Dimensions	H	mm	290			290			315		
	W	mm	799			799			1,019		
	D	mm	181			181			180		
Net Operating weight		kg	8			8			12		
Water connections	Type		Threaded male connection								
	Diameter (nominal)		1/2"			1/2"			1/2"		
Nominal cooling capacity based on: 7°C EWT - Indoor air temp. 27°C DB / 19°C WB						Nominal heating capacity based on: 45°C EWT - Indoor air temp. 20°C DB					

