

Water Cassette

PRODUCT:

- Four way air flow system
- Quiet turbo fan
- Low under-ceiling height



Models			HKH-HKW-HKY					
			25			35		
		Fan speed	HS	MS	LS	HS	MS	LS
Cooling capacity	Total capacity	kW	6.90	5.70	4.60	9.90	8.20	6.50
	Water flow	l/h	1,190			1,700		
	Pressure drop	kPa	35			48		
Heating capacity (2 tube)	Capacity	kW	9.40	7.80	6.20	13.50	11.20	8.90
	Water flow	l/h	1,190			1,700		
	Pressure drop	kPa	17			26		
Fan section	Air flow	m ³ /h	1,260	1,050	830	1,800	1,500	1,200
Acoustics	Noise level	dB(A)	44	42	39	44	42	39
Electrical characteristics	Power supply	V/Ph/Hz	220-240/1/50 or 208-230/1/60					
		Hz	50	60	50	60		
	Power input	W	118	169	151	195		
	Nominal current	A	0.56	0.80	0.71	0.91		
Controls			Infrared remote control with LCD display					
Dimensions (Unit/Panel)	H	mm	290/40			340/40		
	W	mm	710/880			810/980		
	D	mm	710/880			810/980		
Net Operating weight		kg	30			41		
Water connections	Type	Male gas						
	Diameter (nominal)	1/2"			3/4"			
Nominal cooling capacity based on: 7°C EWT - 12°C LWT - Indoor air temp. 27°C DB / 19°C WB						Nominal heating capacity based on: 50°C LWT - Indoor air temp. 20°C DB		

035T73014-001



BE-HK0101-17